
## **LUMANTIX-P**



Decorative post-top luminaire with classic mushroom form.

Its MLT version (Multi-Lens Technology), consisting of highly efficient UV and temperature-resistant lens systems in 4-fold configuration with symmetric wide light intensity distribution for illuminating paths, especially cycle paths. Further beam characteristics are available for flexible adaptation to customerspecific lighting tasks.

Luminaire body of cast aluminium and canopy of corrosion-resistant aluminium. Diffusers of highly impact-resistant clear PMMA.





Input Power	Size W (mm)	н)	Weight (Kg)	Rated Voltage (V)	Power Factor	ATHD	Input Frequency	Efficacy* (Lm/W)	CCT**	CRI
LUMANTIX - P 25W	570	606	7.5	240	>0.95	<10%	50Hz	100	WW/NW/CW	70
LUMANTIX - P 35W	570	606	7.5	240	>0.95	<10%	50Hz	100	WW/NW/CW	70

<sup>\*</sup> For NW/CW only. Option available in 110Lm/W




<sup>\*\*</sup> WW: 3000K, NW: 4000K, CW: 5700K. Other CCTs also available on request

## Material & Finish

- Housing Pressure Die Cast Aluminium / Spun aluminium canopy
- Protector Clear PMMA
- Finish Powder coated Grey

## Installation & Mounting 3 - 6m

 Mounting on 76mm OD diameter pipe





IS 10322 (Part 5/Sec 3):2012 R-91003158 www.bis.gov.in


IP65

**IK07** 


10KV

>50,000 Hours L70


## **Light Distribution**




Asymmetric



Rotationally Symmetric



Symmetric














Manufacturing: Kesslec Smart Lighting Technologies Private Limited (Formerly Keselec Lighting Private Limited Keselec K) Plot no 55 Industrial Area | N.I.T Faridabad -121001 | Haryana | India E-mail: info@kesslec.com

